diatron



ANALYZER OVERVIEW

The Abacus 5 system is a compact, bench top, 60 test/hour, 5-part laser WBC differential analyzer with two sampling modes: a cap piercing mode for closed tube sampling and another for open tubes. The Abacus 5 can be enhanced to meet your changing needs by adding an autosampler

and / or a small sample volume module. This system is an ideal solution for most hospitals, laboratories and satellite clinics that are looking for more advanced technology which is reliable, safe, accurate and easy to use.

BENEFITS AND KEY FEATURES

ACCURATE AND PRECISE RESULTS

- Proven impedance measurement technology
- Patented optical laser based WBC differential technology
- Clog detection and prevention with automatic system cleaning
- Advanced sample aspiration flagging checks

FIELD UPGRADEABLE OPTIONS

- Autosampler for walk-away capability
- Small Sample Module** for reduced sample volume requirement

USER FRIENDLY AND EASY TO OPERATE

- · High resolution touch screen
- Recording sample and quality control information is fast and efficient
- Information can be uploaded from a USB, QR code or via a bi-directional LIS connection

OPERATOR SAFETY

- Cap piercing mode validated for several sample tube types e.g. Monovette, Vacutainer, Vacuette
- BD MAP tube can be used if small sample module fitted
- Self-cleaning minimizes daily maintenance
- · Reduced risk of biohazard exposure

CONFIDENCE

- Simple warning messages and sample flags
- On-board comprehensive QC SW package
- Offers (3 levels) of user access rights / authority levels
- Automatically manages on-board reagent status and lot / expiration dates

SPECIFICALLY MATCHED REAGENTS

- Designed to use specific Diatron reagents to deliver the highest quality results
- Maximum shelf life of 36 months with up to 120 day on-board stability

SPECIFICATIONS

MEASURING DATA

- Throughput: 60 tests/hour
- Parameters: CBC+5 DIFF mode, 2 histograms: RBC, PLT, 2 scattergrams: 4 diff, BASO, 26 parameters: WBC, LYM, MON, NEU, EOS, BAS, LYM%, MON%, NEU%, EOS%, BAS%, RBC, HCT, MCV, RDW-sd, RDW-cv, HGB, MCH, MCHC, PLT, PCT*, MPV, PDW-sd*, PDW-cv*, P-LCC*, P-LCR*

MEASURING PRINCIPLE

- Laser light scatter technology
- Impedance method for CBC
- · Light absorbance for HGB measurement

REAGENTS AND SAMPLING SYSTEM

Samples

- Sample volume: I I 0 µl of whole blood
- Closed and open tube sampling
- Calibration: Stat and Autosampler mode, specific control material (external reference – optional)
- Pre-dilute software option for small samples

Reagents

 Environmentally friendly Diluent and Cleaner reagents and cyanide-free Lyse

QUALITY CONTROL

- Separate QC database
- Levey-Jennings graphs

TECHNICAL FEATURES

- Multilevel user modes with individual identification
- Data storage capacity: 100,000 records
- Printout: External printers

USAGE

- User interface: LCD touch screen (10.4")
- Multilingual user interface English, French, Spanish, Croatian, Hungarian, Italian, Polish, Portuguese, Russian, Turkish, Chinese, German, Greek

DIMENSIONS

- Size (Width x Depth x Height)
 40 cm x 50 cm x 45 cm
 16" x 20" x 18"
- Weight: 35 kg, 77 lbs

OPTIONS

Autosampler

- · Sample capacity: 100 tubes with continuous loading
- Acceptable primary tubes Greiner, Monovette, Terumo, Vacuette, Vacutainer
- Built-in barcode reader and sample mixer
- Cap recognition

Small sample module *

- Aspirated sample only 25 μl (standard 110 μl)
- Parameter/feature not available in the US

Analyzers and Upgrade kits

Description	Catalogue No	SAP Cat. No
Abacus 5 with sample tube cap piercing	A5-I	10021849
Abacus 5 with Autosampler module	A5AS-I	10022017
Abacus 5 with Small Sample Volume module	A5SSM-I	10022045
Small Sample Volume mod- ule - Upgrade kit (for units pre 5/13)	A5SSM-Kit	10030744
Small Sample Volume mod- ule - Upgrade kit (fur units post 4/13)	A5SSM01-Kit	10033068
Autosampler module - Up- grade kit	AS5-I	10022494

Reagents for Abacus 5

SAP Cat. No	Cat. No.	Product name	Pack size
10023088	D1512	Diatro•Dil-5P	20 1
10023190	D3015HK	Diatro•Lyse-5P with Hardware Key	51
10023204	D3021	Diatro•Diff-5P	1.1
10023301	D8011	Diatro•Hypoclean CC	100 m



We are a member of the STRATEC Group | www.diatron.com | sales@diatron.com

Abacus 5 is available for sale in all markets-US and non-US.

Diatron MI Zrt makes best efforts to provide accurate information and specifications herein, whereby it may be possible for omissions or errors to have occurred. Diatron MI Zrt shall have no liability for the accuracy and completeness of the information and cannot be held liable for any representations or warranties, expressed or implied, and any third party claims or losses of any damages. Diatron MI Zrt reserves the right to make any changes to the information, including specifications, without notice. The applications and products herein may not be available in all markets. ©2019, Diatron MI Zrt. Hungary, all rights reserved.

Version Nr. A5190528V9

